

# Technical data sheet

## Wiring trunking, type LK4 N 80060

Item number: 6178229



Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tapering in the side slots prevents the cables from falling out. Tested to DIN EN 50085-2-3. Special lengths on request.



**PVC** Polyvinylchloride

### Master data

|                     |                               |
|---------------------|-------------------------------|
| Item number         | 6178229                       |
| Type                | LK4 N 80060                   |
| Description 1       | Slotted cable trunking system |
| Manufacturer        | OBO                           |
| Dimension           | 80x60x2000                    |
| Colour              | Stone grey; RAL 7030          |
| Material            | Polyvinylchloride             |
| Smallest sales unit | 2                             |
| Unit of quantity    | Metre                         |
| Weight              | 82 kg                         |
| Weight unit         | kg/100 m                      |


# Technical data sheet

## Wiring trunking, type LK4 N 80060

Item number: 6178229



### Dimensions



|        |          |
|--------|----------|
| Length | 2,000 mm |
| Width  | 60 mm    |
| Height | 80 mm    |

### Technical data

|                                   |                       |
|-----------------------------------|-----------------------|
| Side wall version                 | Slotted               |
| Fastening type                    | Base perforation      |
| Flexible                          | no                    |
| Halogen-free                      | no                    |
| Creepage current-resistant        | yes                   |
| With cover                        | yes                   |
| Usable cross-section              | 45.86 cm <sup>2</sup> |
| Slot spacing                      | 12.5 mm               |
| Slot width                        | 5 mm                  |
| Self-extinguishing                | yes                   |
| Permitted temperature range, max. | 60 °C                 |
| Permitted temperature range, min. | -5 °C                 |