

# Technical data sheet

## US 3 suspended support FTK black

Item number: 7265690



Suspended support (U profile) in the dimensions of 50 x 30 mm with welded-on head plate. For fastening to horizontal concrete ceilings and steel girders. Powder-coated in jet black (RAL 9005) From a bracket width of 400 mm or when the bracket is mounted on the end of the suspended support, it is recommended to use the spacer type DSK 25.



|      |                    |
|------|--------------------|
| St   | Steel              |
| P135 | PES135 - Polyester |

### Master data

|                     |                        |
|---------------------|------------------------|
| Item number         | 7265690                |
| Type                | US 3 K 20 FTK SW       |
| Description 1       | Support                |
| Description 2       | with welded head plate |
| Manufacturer        | OBO                    |
| Dimension           | 50x30x200              |
| Colour              | Jet black; RAL 9005    |
| Material            | Steel                  |
| Surface             | PES135 - Polyester     |
| Surface standard    |                        |
| Smallest sales unit | 1                      |
| Unit of quantity    | Piece                  |
| Weight              | 60.9 kg                |
| Weight unit         | kg/100 pc.             |


# Technical data sheet

US 3 suspended support FTK black

Item number: 7265690



## Dimensions



|                 |         |
|-----------------|---------|
| Length          | 200 mm  |
| Length          | 0.65 ft |
| Width           | 50 mm   |
| Height          | 30 mm   |
| Plate thickness | 0.08 in |
| Dimension L     | 200 mm  |

## Technical data

|                               |           |
|-------------------------------|-----------|
| Version for                   | U profile |
| Bracket length 200            | 2.7 kN    |
| Bracket length 400            | 1.5 kN    |
| Maintain electrical functions | no        |
| Material thickness            | 2 mm      |
| Maximum tensile load          | 5 kN      |