

Technical data sheet

US 3 suspended support FTK black

Item number: 7265696



Suspended support (U profile) in the dimensions of 50 x 30 mm with welded-on head plate. For fastening to horizontal concrete ceilings and steel girders. Powder-coated in jet black (RAL 9005) From a bracket width of 400 mm or when the bracket is mounted on the end of the suspended support, it is recommended to use the spacer type DSK 25.



St	Steel
P135	PES135 - Polyester

Master data

Item number	7265696
Type	US 3 K 40 FTK SW
Description 1	Support
Description 2	with welded head plate
Manufacturer	OBO
Dimension	50x30x400
Colour	Jet black; RAL 9005
Material	Steel
Surface	PES135 - Polyester
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	75 kg
Weight unit	kg/100 pc.


Technical data sheet

US 3 suspended support FTK black

Item number: 7265696



Dimensions



Length	400 mm
Length	1.31 ft
Width	50 mm
Height	30 mm
Plate thickness	0.08 in
Dimension L	400 mm

Technical data

Version for	U profile
Bracket length 200	2.7 kN
Bracket length 400	1.5 kN
Maintain electrical functions	no
Material thickness	2 mm
Maximum tensile load	5 kN