

Technical data sheet

Trunking, type WDK 20020 with base perforation

Item number: 6025155



Wall and ceiling trunking, halogen-free, consisting of cover and base for mounting directly on the wall.
During installation, ensure that only halogen-free accessories and fastening materials are used.



PVC Polyvinylchloride

Master data

Item number	6025155
Type	WDK20020SW
Description 1	Wall trunking system
Description 2	with base perforation
Manufacturer	OBO
Dimension	2000x20x20
Colour	Jet black; RAL 9005
Material	Polyvinylchloride
Smallest sales unit	48
Unit of quantity	Metre
Weight	11 kg
Weight unit	kg/100 m

Dimensions

Length	2,000 mm
Width	17.5 mm
Height	17.5 mm

Technical data sheet

Trunking, type WDK 20020 with base perforation

Item number: 6025155



Technical data

Number of fixed partitions	0
Number of cables NYM 3 x 1.5 mm ² Ø 10.5 mm (without socket)	1
Number of cables NYM 3 x 2.5 mm ² Ø 11.5 mm (without socket)	1
Number of cables NYM 5 x 1.5 mm ² Ø 12.0 mm (without socket)	1
Number of insertable partitions	0
Version, cable trunking cover	Loose
Fastening type	Base perforation
Maintain electrical functions	no
Halogen-free	no
Cable retaining clip	no
Duct connector	no
Delivery on a roll	no
Usable cross-section	220 mm ²
Protection rating	IP30
Protective film	no
Protection rating IK code	IK04
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C