Technical data sheet Trunking, type WDK 40090

Item number: 6021023





Wall and ceiling trunking, halogen-free, consisting of cover and base for mounting directly on the wall.

During installation, ensure that only halogen-free accessories and fastening materials are used.

Four cover clips included

Lid clip can be moved along the entire length of the trunking.



PVC

Polyvinylchloride

B 4	4-		-4-
IVI	aste	г о	ата

Item number	6021023
Туре	WDK40090SW
Description 1	Wall trunking system
Description 2	with base perforation
Manufacturer	OBO
Dimension	2000x90x40
Colour	Jet black; RAL 9005
Material	Polyvinylchloride
Smallest sales unit	32
Unit of quantity	Metre
Weight	78.1 kg
Weight unit	kg/100 m

Dimensions

	Length	2,000 mm
	Width	90 mm
	Height	40 mm

Technical data sheet Trunking, type WDK 40090





Technical data

Number of fixed partitions	0
Number of cables NYM 3 x 1.5 mm ² Ø 10.5 mm (without socket)	15
Number of cables NYM 3 x 2.5 mm ² Ø 11.5 mm (without socket)	12
Number of cables NYM 5 x 1.5 mm ² Ø 12.0 mm (without socket)	11
Number of insertable partitions	1
Version, cable trunking cover	Loose
Fastening type	Base perforation
Maintain electrical functions	no
Halogen-free	no
Cable retaining clip	yes
Duct connector	no
Delivery on a roll	no
Usable cross-section	2656 mm²
Protection rating	IP30
Protective film	no
Protection rating IK code	IK04
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C