



Fastening with no risk of damage. Mounting made easier and faster.



OBO universal adapter for the direct fastening of plastic trunking

Quick and clean plastic trunking mounting – without damage from setting: The new universal adapter from OBO expands your options for fastening WDK cable trunking significantly.

The adapter was designed specifically for fastening plastic

trunking to walls using a setting tool. It reliably absorbs the energy generated during setting and protects the trunking from cracks, deformation and visible damage.

The result is a safe, clean and permanently stable fastening – plus fast mounting.

Your advantages at a glance

- Fastening of standard plastic trunking with the setting tool with no risk of damage
- Absorbs setting energy, reliably protecting the trunking
- Fast direct mounting – fewer steps on the construction site
- Compatible with all standard setting tools (e.g. Hilti, Würth, Spit, Fischer, Bosch)
- Designed specifically for the OBO WDK portfolio

www.obo-bettermann.com

One adapter. Many options.

In combination with OBO plastic trunking, the universal adapter functions as the trunking fastening, increasing installation efficiency significantly.

Suitable for:

- All WDK trunking types from a trunking width of 30 mm
- Rapid-80 trunking

Mounting tip:

For optimal results, do not position the adapter on the solid material of the trunking during setting. Instead, use the slots in the trunking.



More than trunking fastening – the principle of the Grip M UNI collection clamp

With the patented universal adapter, the Grip M UNI collection clamp does even more: Besides fast installation with one hand using the setting tool, it also enables classic screw fitting via the integrated 6.5 mm fastening hole – for maximum flexibility on the construction site.

Additional system benefits

- Fast, single-handed mounting
- One system for wall and ceiling
- Can be opened and closed without tools
- Freedom to choose between direct fastening and screw fitting

On the safe side, even in the event of fire

Both cable routing with the UNI collection clamp for direct fastening using a setting tool and classic screw fitting are permitted as cable-specific routing systems for the maintenance of electrical function classes E30, E60 and E90, in accordance with DIN 4102 Part 12. *

* Observe the installation parameters from the general construction test certificate depending on the tested cables.



OBO Bettermann Holding GmbH & Co. KG
Hüingser Ring 52
58710 Menden
GERMANY

Customer Service Germany
Tel. +49 (0)2373 89-2000
info@obo.de
www.obo-bettermann.com